## DuraLed Plus



Vision and Innovation

#### **INSTRUCTION SHEET**

## Efficient and Powerful White LED Lighting

#### Introduction

Hella marine LED lamps offer many advantages over conventional bulb lamps including significantly reduced power consumption, and a high tolerance to shock and vibration for an ultra long service life.

DuraLed® Plus lamps represent that latest in class leading high efficacy LED lighting that is both ultra durable and ultra powerful for heavy duty marine interior and exterior applications.

#### Installation


#### Screw Cap Removal

Carefully insert a small flat blade screwdriver between the cap and the lens and pull towards the lens, the cap will clip off.

To install the cap push in by hand until the top is flush with the lens.

#### Surface Mounting

- Drill two holes up to 6.5mm Ø at 148mm centres.
- 6mm Ø screws or bolts are recommended to mount the lamp using the mounting bushes provided.
- Lamp should be mounted on a flat surface.
- If passing the cable through a hole, ensure there are no sharp edges to cut or chafe the cable.
- Alternatively, cable can be routed through the end of the base.
- Connect cable as per chart below.
- Clip the screw caps on securely until flush with the lamp surface



Note: Bolts not

Note: When mounting lamp units side by side allow a gap of 5mm to ensure screw cap removal.

#### Wiring Colour Coding

LED modules are polarity conscious.

Reverse polarity will not damage this product but will inhibit its function.

Hella marine recommends wire connections be soldered, and heat shrink tubing applied to seal the joint.

Colour	Connect to	Power Consumption
Black	Negative (-)	
Red	Signal (+)	< 9 watts

NB: Lamp must be protected by a fuse rated at 5 amperes maximum.

# DuraLed Plus



Vision and Innovation

#### **INSTRUCTION SHEET**

### Efficient and Powerful White LED Lighting

#### Introduction

Hella marine LED lamps offer many advantages over conventional bulb lamps including significantly reduced power consumption, and a high tolerance to shock and vibration for an ultra long service life.

DuraLed® Plus lamps represent that latest in class leading high efficacy LED lighting that is both ultra durable and ultra powerful for heavy duty marine interior and exterior applications.

#### Installation


#### Screw Cap Removal

Carefully insert a small flat blade screwdriver between the cap and the lens and pull towards the lens, the cap will clip off.

To install the cap push in by hand until the top is flush with the lens.

#### Surface Mounting

- Drill two holes up to 6.5mm Ø at 148mm centres.
- 6mm Ø screws or bolts are recommended to mount the lamp using the mounting bushes provided.
- Lamp should be mounted on a flat surface.
- If passing the cable through a hole, ensure there are no sharp edges to cut or chafe the cable.
- Alternatively, cable can be routed through the end of the base.
- Connect cable as per chart below.
- Clip the screw caps on securely until flush with the lamp surface



Note: Bolts not

Note: When mounting lamp units side by side allow a gap of 5mm to ensure screw cap removal.

#### Wiring Colour Coding

150-03 V03

LED modules are polarity conscious.

Reverse polarity will not damage this product but will inhibit its function.

Hella marine recommends wire connections be soldered, and heat shrink tubing applied to seal the joint.

Colour	Connect to	Power Consumption
Black	Negative (-)	
Red	Signal (+)	< 9 watts

NB: Lamp must be protected by a fuse rated at 5 amperes maximum.

## DuraLed Plus



Vision and Innovation



#### **Electromagnetic Compatibility (EMC)**

This Multivolt LED lamp is an electronic device. The electrical circuits contain components that suppress possible interference, both emission as well as susceptibility, to the limits prescribed in EN 60945.

#### Protection against damage due to voltage spikes

This lamp is protected against reverse polarity connection and negative voltage spikes of up to -1000 volts.

Lens material UV resistant, enhanced impact acrylic

Base material UV and impact resistant plastic

Light Source LED

**Colour Temperature** 5000K (Cool White) **Dimming** Cannot be dimmed

Cable Pre-wired with 2.5m of twin core marine cable. UL listed.

Operating Voltage 9-33V DC

Voltage Protection Spike protected to +500 volts

Reverse polarity protected to -700 volts

**Power Consumption** < 9W ( < 0.75A @ 12V / < 0.375A @ 24V )

Degree of Protection IP 67 - Completely sealed


Weight 345g (including cable)

**Installation** Surface mount with robust bush mount

**Approvals** CE

ISO 8846 (Ignition Protection)

#### **General Dimensions (mm)**



### **Warranty Statement**

Congratulations! The product you have selected comes from Hella marine - one of the world's leading manufacturers marine lighting products.

Hella marine branded products are covered by a warranty against manufacturing or material defects. (For further details please check the terms of trade with your Hella marine agent).

The lamp module is sealed and does not have any serviceable parts inside; opening the module will invalidate warrantv.

In the unlikely event that you should experience a problem with your purchase, please contact your Hella marine agent where you purchased the product.



## DuraLed Plus



Vision and Innovation



#### **Electromagnetic Compatibility (EMC)**

This Multivolt LED lamp is an electronic device. The electrical circuits contain components that suppress possible interference, both emission as well as susceptibility, to the limits prescribed in EN 60945.

#### Protection against damage due to voltage spikes

This lamp is protected against reverse polarity connection and negative voltage spikes of up to -1000 volts.

Lens material UV resistant, enhanced impact acrylic

Base material UV and impact resistant plastic

Light Source LED

**Colour Temperature** 5000K (Cool White) **Dimming** Cannot be dimmed

Cable Pre-wired with 2.5m of twin core marine cable. UL listed.

Operating Voltage 9-33V DC

**Voltage Protection** Spike protected to +500 volts

Reverse polarity protected to -700 volts

**Power Consumption** < 9W ( < 0.75A @ 12V / < 0.375A @ 24V )


Degree of Protection IP 67 - Completely sealed Weight 345g (including cable)

**Installation** Surface mount with robust bush mount

Approvals CE

ISO 8846 (Ignition Protection)

#### **General Dimensions (mm)**



### **Warranty Statement**

Congratulations! The product you have selected comes from Hella marine - one of the world's leading manufacturers marine lighting products.

Hella marine branded products are covered by a warranty against manufacturing or material defects. (For further details please check the terms of trade with your Hella marine agent).

The lamp module is sealed and does not have any serviceable parts inside; opening the module will invalidate warrantv.

In the unlikely event that you should experience a problem with your purchase, please contact your Hella marine agent where you purchased the product.

